Specifications



MN undervoltage release, ComPact NS630b to NS3200 fixed, MasterPact NT/NW, rated voltage 200/250 VDC, 200/250 VAC 50/60 Hz

33671

Main

| Range | ComPacT |
|-------------------------------|---|
| Range Of Product | ComPacT NS630b1600 new generation ComPacT NS1600b3200 new generation |
| Device Short Name | MN |
| Product Or Component Type | Voltage release |
| Device Application | Control |
| Voltage Release Type | Opening coil Undervoltage release |
| Control Type | Standard |
| [Uc] Control Circuit Voltage | 200250 V AC 50/60 Hz 200250 V DC |
| Circuit Breaker Mounting Mode | Fixed |
| Range Compatibility | ComPact ComPact NS630b1600 ComPact ComPact NS1600b3200 |

Complementary

| Operating Threshold | 0.350.7 x Un opening 0.85 x Un closing |
|---------------------------------------|---|
| Response Time | 90 ms +/- 5 % for Compact NS630b1600 90 ms +/- 5 % for Compact NS1600b3200 40 ms +/- 5 % for MasterPact NT 90 ms +/- 5 % for MasterPact NW |
| Supply Holding Power | 4.5 VA |
| Accessory / Separate Part Category | Spare part for MasterPact NT Spare part for MasterPact NT NAVY Spare part for MasterPact NW Spare part for MasterPact NW NAVY Spare part for ComPacT NS630b1600 new generation Spare part for ComPacT NS1600b3200 new generation |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|--------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 3.5 cm |
| Package 1 Width | 6.0 cm |
| Package 1 Length | 8.1 cm |

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

| Package 1 Weight | 150.0 g |
|------------------------------|-----------|
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 10 |
| Package 2 Height | 9.0 cm |
| Package 2 Width | 13.0 cm |
| Package 2 Length | 18.5 cm |
| Package 2 Weight | 1.6 kg |
| Unit Type Of Package 3 | S03 |
| Number Of Units In Package 3 | 120 |
| Package 3 Height | 30.0 cm |
| Package 3 Width | 30.0 cm |
| Package 3 Length | 40.0 cm |
| Package 3 Weight | 19.435 kg |

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| Mercury Free | |
|----------------------------|---|
| Rohs Exemption Information | Yes |
| | |
| Reach Regulation | REACh Declaration |
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| | Product out of China RoHS scope. Substance declaration for your information |