



1021001100

VSS-MP

VSS Master Panel - V2 This item has been replaced by Phontech Sound Reception System


This product will be replaced by the equivalent Phontech solution, but Zenitel will honor prior commitments given to the market. Therefore, we will continue to provide expansion and spare-part service for this product.

Description

The Sound Reception System (VSS-V2) is a navigation aid system required on ships with enclosed bridges. The system allows the officer in charge of the navigational watch to hear sound signals and determine their direction. The VSS-V2 system conforms to MED, ISO14859 and DNV2012 rules.

- Active noise cancelling and tone detection based on DSP technology
- Dimmer and adjustable backlight
- Sector indication via 8 LEDs
- Ocentral microphone unit with 4 directional microphones for mounting on top of the wheelhouse
- Max. ambient noise level 70dB
- Web interface for system operation
- Output for voyage data recorder
- Remote muting when typhoon/foghorn or Public Address system is activated
- Override function to hear unfiltered sound from microphone unit
- Able to connect up to 4 slave panels
- NEW: Reverse LED indication functionality. See manual for details. From revision 2.06

Technical Dimensions



Specifications

GENERAL

| Dimensions (WxHxD) | 280 x 140 x 90 mm |
|---|---|
| Mounting | Flush |
| Housing | Brushed aluminum with foil |
| IP rating | IP-22 |
| Operation voltage | 24 V DC |
| Audio | 70 Hz to 2'100 Hz Active noise cancellation Adjustable volume Squelch to adjust the automatic threshold |
| LEDs | 8 |
| Buttons | Power, Override, Squelch, Dimmer, Volume |
| Operation voltage | 24V DC +30% / -10% |
| Current load Master panel & Microphone unit / Including 1 slave panel | Max. 200mA / Max. 270mA |
| Weight | 1.6 kg |
| | |

Used With





VSS-SP

VSS Slave Panel - V2 This item has been replaced by Phontech Sound Reception System

VSS-MU

VSS Microphone Unit - V2 This item has been replaced by Phontech Sound Reception System