

M.3

hex 24

hidra[matic]

Downloaded from: www.hidramatic.com



0166

Diaphragm pressure switches up to 42 V with M3 screw terminal

- Made of zinc-plated steel (CrVI-free)
- M3 screw terminal
- Overpressure safety up to 300 bar¹⁾

Adjustment range tolerance at room temperature	Male thread	Order number NO → :	Order number NC → :
---	----------------	-------------------------	------------------------

0166 Diaphragm pressure switches with M3 screw terminal

0.1 – 1 (±0.2) bar	G 1/4	0166 – 401 03 – X – 003	0166 – 402 03 – X – 007
	G 1/8	0166 – 401 28 – X – 601	0166 – 402 28 – X – 602
	M 10x1 cyl.	0166 – 401 13 – X – 001	0166 – 402 13 – X – 002
	M 10x1 con.	0166 – 401 01 – X – 001	0166 – 402 01 – X – 005
	M 12x1.5 cyl.	0166 – 401 02 – X – 002	0166 – 402 02 – X – 006
	NPT 1/8	0166 – 401 04 – X – 004	0166 – 402 04 – X – 008
0.5 – 3 (±0.3) bar	G 1/4	0166 – 421 03 – X – 070	0166 – 422 03 – X – 070
	G 1/8	0166 – 421 28 – X – 070	0166 – 422 28 – X – 070
	M 10x1 cyl.	0166 – 421 13 – X – 070	0166 – 422 13 – X – 070
	M 10x1 con.	0166 – 421 01 – X – 070	0166 – 422 01 – X – 070
	M 12x1.5 cyl.	0166 – 421 02 – X – 070	0166 – 422 02 – X – 070
	NPT 1/8	0166 – 421 04 – X – 070	0166 – 422 04 – X – 070
1 – 10 (±0.5) bar	G 1/4	0166 – 405 03 – X – 019	0166 – 406 03 – X – 023
	G 1/8	0166 – 405 28 – X – 605	0166 – 406 28 – X – 606
	M 10x1 cyl.	0166 – 405 13 – X – 005	0166 – 406 13 – X – 006
	M 10x1 con.	0166 – 405 01 – X – 017	0166 – 406 01 – X – 021
	M 12x1.5 cyl.	0166 – 405 02 – X – 018	0166 – 406 02 – X – 022
	NPT 1/8	0166 – 405 04 – X – 020	0166 – 406 04 – X – 024
10 – 20 (±1) bar	G 1/4	0166 – 409 03 – X – 035	0166 – 410 03 – X – 039
	G 1/8	0166 – 409 28 – X – 609	0166 – 410 28 – X – 610
	M 10x1 cyl.	0166 – 409 13 – X – 009	0166 – 410 13 – X – 010
	M 10x1 con.	0166 – 409 01 – X – 033	0166 – 410 01 – X – 037
	M 12x1.5 cyl.	0166 – 409 02 – X – 034	0166 – 410 02 – X – 038
	NPT 1/8	0166 – 409 04 – X – 036	0166 – 410 04 – X – 040
20 – 50 (±2) bar	G 1/4	0166 – 413 03 – X – 051	0166 – 414 03 – X – 055
	G 1/8	0166 – 413 28 – X – 613	0166 – 414 28 – X – 614
	M 10x1 cyl.	0166 – 413 13 – X – 013	0166 – 414 13 – X – 014
	M 10x1 con.	0166 – 413 01 – X – 049	0166 – 414 01 – X – 053
	M 12x1.5 cyl.	0166 – 413 02 – X – 050	0166 – 414 02 – X – 054
	NPT 1/8	0166 – 413 04 – X – 052	0166 – 414 04 – X – 056

Seal material – Application areas

NBR	Hydraulic/machine oil, heating oil, air, nitrogen, etc.	1
EPDM	Brake fluid, hydrogen, oxygen, acetylene, etc.	2
FKM	Hydraulic fluids (HFA, HFB, HFD), petrol/gasoline, etc.	3
HNBR	Hydraulic/machine oil, ester-based bio-oils	9

Refer to page 41 for the temperature range and application thresholds of sealing materials.



Your order number:

0166 – XXX XX – X – XXX



¹⁾ Static value. Dynamic value is 30-50 % lower. Values pertain to the hydraulic/pneumatic part of the pressure switch.



- Most cost-effective solution for mechanical pressure monitoring
- Stable switching point even after long use and high load
- Switching point can be adjusted when fitted on site ¹⁾
- High pressure resistance, compact, small switches, available as normally closed (NC) or normally open (NO)
- For solutions with integrated connectors please refer to chapter M.1, starting at page 22

¹⁾ Pressure switches can also be supplied preset at factory. Our preset switches are sealed with lacquer paint, set points are embossed on the housing.

Pressure switches hex 24

Technical data

M.3

hex 24

hidra[**matic**]

Downloaded from: www.hidramatic.com



Rated working voltage:	10 ... 42 VAC/DC	
Rated current range (resistive load, 12 DC and 12 AC):	10 mA ... 4 A	
Switching power DC12 / AC12:	100 W / 100 VA	
Temperature resistance of sealing materials:	NBR	-40 °C ... +100 °C
	EPDM	-30 °C ... +120 °C
	EPDM-W270, diaphragm	-20 °C ... +100 °C
	FKM (in diaphragm pressure switch)	-5 °C ... +120 °C
	FKM (in piston pressure switch)	-10 °C ... +120 °C
	Silicone, diaphragm	-40 °C ... +120 °C
	HNBR	-30 °C ... +120 °C
Switching frequency:	200 / min.	
Mechanical life expectancy:	1,000,000 cycles (for diaphragm pressure switches, life expectancy value only applies for switching pressures to max. 50 bar)	
Pressure rise rate:	≤ 1 bar/ms	
Hysteresis:	Average value 5 – 30 % depending on type, not adjustable	
Vibration resistance:	10 g; 5 – 200 Hz sine wave; DIN EN 60068-2-6	
Shock resistance:	294 m/s ² ; 14 ms half sine wave; DIN EN 60068-2-27	
Protection class:	IP65 Terminals IP00	
Weight:	approx. 90 g	

Type:		0163	0164	0166	0167	0168	0169
Material:	Zinc-plated steel (CrVI-free)	●		●		●	●
	Stainless steel		●				
	Brass				●		
Overpressure safety up to:	35 bar				●		
	300 bar			●		●	
	600 bar	●	●				●



M