

RECHARGEABLE

INTRINSICALLY SAFE DUAL-LIGHT™ FLASHLIGHT

XPR-5542GMX

NIGHTSTICK
Life Depends on Light™



DUAL-LIGHT™

275-lumen Dual-Light™ provides simultaneous **flashlight and floodlight** operation

IP-X7
WATER
PROOF

INTEGRATED
HEAVY-DUTY
MAGNET

400 LUMENS



Large, textured buttons that are **easy-to-use with gloves**



Durable polymer body is **impact & chemical resistant**



Non-conductive body designed for hazardous environments



Powerful base magnet allows "hands-free" use



1-800-233-2155 · 1-469-326-9400 · nightstick.com

DUAL-LIGHT™ FLASHLIGHT

RECHARGEABLE

ITEM NUMBER/UPC

XPR-5542GMX - 017398806008

CERTIFICATIONS

- cULus
- ATEX
- IECEX
- Kosha
- CE
- BC

CASE MATERIAL

- ABS Polymer

LUMENS/RUNTIME

SPOTLIGHT

- HIGH: 400 lumens, 10 hrs runtime

FLOODLIGHT

- HIGH: 225 lumens, 11 hrs runtime

DUAL-LIGHT

- 275 lumens, 10 hrs runtime

CANDELA

- HIGH: 11571

BEAM DISTANCE

- HIGH: 215m

WATER RATING

- IP-67 (dust-proof/waterproof)

DROP RATING

- 2m

DIMENSIONS

- LENGTH: 9.5 in (241 mm)
- BARREL DIAMETER: 1.2 in (30 mm)
- BEZEL DIAMETER: 1.6 in (40 mm)
- WEIGHT: 10.9 oz (309 g)

BATTERY







- Integrated li-ion battery

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Light with li-ion rechargeable battery
- Snap-in rapid charger
- AC/DC power supplies
- Anti-roll ring
- Instruction manual

FL 1 STANDARD	FLASH HIGH	FLASH LOW	DUAL-LIGHT
	400 LUMENS	80 LUMENS	275 LUMENS
	10h	41h	10h
	215m		
	11571cd		
	2m		
	1m		

Bayco Products, Inc.
Wylie, TX 75098
XPR-5542

Ex ia FLASHLIGHT FOR USE IN
HAZARDOUS LOCATIONS
UL listed for use with Bayco Li-ion Battery
Pack 5500-BATT



E 467756
ID 5012927
INTRINSICALLY SAFE
SECURITE INTRINSEQUE



ZZ-AV480-0248X



SEE INSTRUCTION MANUAL
VOIR MANUEL

US Patent 9.713.217

CLASS I DIV 1 GRPS A-D T4
CLASS II & III DIV 1 GRPS E-G
CLASS I ZONE 0 GRP IIC T4
CLASS II ZONE 20 IIC T135°C

Ex ia IIC T4 Gb
Ex ia IIC T4 Gb
DEMKO 16 ATEX 1815
IECEX UL 16.0168
-20°C ≤ Tamb ≤ +40°C
3.7V/Cell 5500-BATT
U_n = 4.75V

MFG MM-YY

CERTIFIED

