

HITESTER 3030-10

Not CE marked

Product warranty for 3 years
Accuracy guaranteed for 1 year



CAT III 600 V

CARRYING CASE 9390



Order code **3030-10**

Accessories



- TEST LEAD L9207-30
- CARRYING CASE 9390
- R6P manganese battery x2
- Spare fuse
- Instruction manual

L9207-30



Measurement parameters	DC Voltage	0.3 V/3 V/12 V/30 V/120 V/300 V/600 V Accuracy: $\pm 2.5\%$ of f.s. reading
	AC Voltage	12 V/ 30 V/120 V/300 V/600 V Accuracy: $\pm 2.5\%$ of f.s. reading, (12V: $\pm 4\%$)
	DC Current	60 μ A/30 mA/300 mA Accuracy: $\pm 3\%$ of f.s. reading
	Resistance	0 to 3k Ω , R \times 1/ R \times 10/ R \times 100/ R \times 1k Accuracy: $\pm 3\%$ of scale length
	Battery check	0.9 to 1.8 V Accuracy: $\pm 6\%$ of f.s. reading
Other	Operating temperature	0°C to 40°C (non-condensating)
	Storage temperature	-10°C to 50°C (non-condensating)
	Power supply	R6P manganese battery x2
	Dimensions (W x H x D)	95 x 141 x 39 mm (3.74 x 5.55 x 1.54 in)
Weight	280 g (9.9 oz)	

CARD HITESTER 3244-60

CE

Product warranty for 3 years
Accuracy guaranteed for 1 year



CAT III 300V, CAT II 600V

CARRYING CASE C0204



Cord length
46cm (1.51 ft)

Order code **3244-60**

Accessories

- CARRYING CASE C0204
- Sleeves (Red, Black @ 1 each)
- CR2032 coin type battery x1
- Instruction manual



Measurement parameters	DC Voltage	420.0 mV/ 4.200 V/ 42.00 V/ 420.0 V/ 500 V Accuracy: $\pm 0.7\%$ rdg ± 4 dgt.
	AC Voltage	4.200 V/ 42.00 V/ 420.0 V/ 500 V Accuracy: $\pm 2.3\%$ rdg ± 8 dgt.
	Resistance	420.0 Ω / 4.200 k Ω / 42.00 k Ω / 420.0 k Ω / 4.200 M Ω / 42.00 M Ω Accuracy: $\pm 2.0\%$ rdg ± 4 dgt.
	Continuity check	Detection level: 50 Ω ± 40 Ω or less
	Operating temperature	0°C to 40°C (non-condensating)
Other	Storage temperature	-20°C to 60°C (non-condensating)
	Power supply	CR2032 coin type battery x1
	Dimensions (W x H x D)	55 x 109 x 9.5 mm (2.17 x 4.29 x 0.37 in)
	Weight	60 g (2.1 oz)

PENCIL HITESTER 3246-60

Not CE marked

Product warranty for 3 years
Accuracy guaranteed for 1 year



CAT IV 300 V, CAT III 600 V

Cord length
80 cm (2.62 ft)



Test lead fits neatly
into back of instrument

Accessories

- Sleeves (Red, Black @ 1 each)
- CR2032 coin type battery x1
- Instruction manual

Order code **3246-60**



Measurement parameters	DC Voltage	420.0 mV/4.200 V/42.00 V/420.0 V/600 V Accuracy: $\pm 1.3\%$ rdg ± 4 dgt.
	AC Voltage	4.200 V/42.00 V/420.0 V/600 V Accuracy: $\pm 2.3\%$ rdg ± 8 dgt.
	Resistance	420.0 Ω /4.200 k Ω /42.00 k Ω /420.0 k Ω /4.200 M Ω /42.00 M Ω Accuracy: $\pm 2.0\%$ rdg ± 4 dgt.
	Continuity check	Detection level: 50 Ω ± 40 Ω or less
	Diode check	Judges the right direction only, Open terminal voltage 3.4 V or less
Other	Operating temperature	0°C to 40°C (non-condensating)
	Storage temperature	-20°C to 60°C (non-condensating)
	Power supply	CR2032 coin type battery x1
	Dimensions (W x H x D)	30 x 182 x 26.5 mm (1.18 x 7.17 x 1.04 in)
Weight	80 g (2.8 oz)	